

FP19 - Portwest 4 Point Comfort Plus**Harness****Collection:** Harnesses**Range:** Height Safety**Materials:** Polyester Webbing, Aluminium, Alloy Steel, Heat Treated**Outer Carton:** 6**Product information**

Ergonomically designed with the users comfort in mind, the 4 Point Comfort Plus Harness has been engineered from lightweight aluminium, optimising strength and durability. It provides 4 points of attachment, one rear D ring, two side D rings and an upper and lower chest D ring. Quick release buckles for easy fitting. Ideal for work positioning or suspension work.

Harnesses

Portwest harnesses are required to ensure protection when working at height. Our range of harnesses offer different connection points that can be used in a variety of job functions such as fall arrest, work positioning, suspension and rescue.

Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

Standards

EN 813:2008

EN 1497:2007

EN 361:2002

EN 358:2018

Features

- Superior strength
- Fully adjustable shoulder, chest and leg straps
- Padded legs, lower back and shoulder straps for added comfort
- Ergonomic quick release buckle
- Max rated load 100kg
- 10 Year shelf life from manufacturing date outlined in product label
- CE certified
- UKCA marked
- Retail box which aids presentation for retail sales



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FP19 - Portwest 4 Point Comfort Plus Harness

Commodity Code: 6307200000

Test House

CCQS Certification Services Ltd. (Notified Body No.: 2834)
Block 1, Blanchardstown Corporate Park
D15 AKK1, Ireland
Cert No: CE-PC-200211-007-17-9B

CCQS UK Ltd (Notified Body No.: 2834)
5 Harbour Exchange
E14 9GE, United Kingdom
Cert No: CA-PC-220322-009-18-9A

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
FP19RER	Red	65.0	45.0	30.0	2.2000	0.0878	5036108280377	15036108770400